CHAMPIONDOOR®

Shipyard and Harbour doors





Shipyard and Harbour doors

The operational reliability, large size and the suitability for buildings of different size makes Champion Door fabric doors especially competitive for shipyards and harbours. The doors are designed according to current EU standards to withstand demanding corrosive conditions and high wind loads. A specially designed PVC material withstands welding sparks. Champion Door offers the market's only specially insulated fabric fold-up door model (NK4 Warm). Thanks to the innovative lift mechanism, the Champion Door doors don't need tracks on the floor nor large frames. This saves in construction costs. Since the components are durable and of high quality, the door's life cycle costs are low.

The doors can be made in any size, and they are available all wind classes. The doors are tailor made according to customer needs and can be delivered installed as a turn-key project if so desired. Close co-operation between the designers and builders guarantees successful door projects and customer satisfaction.





FEATURES

- (wind speed 41 m/s or more)

 NK4 Warm with standard insulation wool
- u-value 0,71 W/(m²•K), with additional insulation up to 0,57 W/(m²•K)
- opening speed 6-10 m/min
- door fabric UV-protected
 weight of door fabric 850 g/m²
- ✓ 24 x 20 m crane door Remontowa, Gdynia, Poland



COLOUR CHOICES

White RAL 9016, Beige RAL 1001, Green RAL 6000, Dark green RAL 6005, Light blue RAL 5012, 5015, Blue RAL 5005, Dark blue RAL 5002, Grey RAL 7035, 7037, 7038, 7024, Brown RAL 8016, Black RAL 9011

◀ Bilfinger Mars Offshore, Poland 35 x 21 m and 35 x 34 m



OPTIONS

- additional insulation
- soundproofingtranslucent fabric
- burglary protection door fabric
- special fabrics for extreme temperatures -60 +200 C
- warning devices (sound signals and blinking lights)
- remote control operating



SPECIAL SOLUTIONS

- hydraulic emergency door open function



MOST IMPORTANT BENEFITS

- lighter structure lower construction cost
 functional reliability in demanding conditions

- low service costsgreat corrosion resistance

TECHNICAL DATA AND OPTIONS

Heat insulation NK4 Warm with standard insulation

wool u-value 0,71 W/(m²•K), with additional insulation up to

0,57 W/(m²•K)

Wind load durability 1 kN/m²

(s) (o) unlimited

Maximum size of door no size limitations

Control system Electronic and programmable (s)

Control from 3 button panel impulse control

radio-control pull switch control radar control

induction loop control

Safety equipment door's falling protection

lower edge crash sensor wind lock photocell

laser – light curtain

Options windows addition heat insulation

soundproofing burglary protection fabric hydraulic emergency open (o) (o)

touch screen operation secure remote control SRC

(s) = standard (o) = option





CHAMPIONDOOR®



Champion Door Oy

Head office / Factory, Hopeatie 2, FI-85500 Nivala, Finland, Phone +358 8 445 8800, Fax +358 8 442 956, info@championdoor.com Bureau de Liaison Paris, 8 rue de Moscou, 75008 Paris, Tél +33 147 202 314, france@championdoor.com Liaison Office UAE, P.O. Box 263038, Dubai, UAE, Tel. +971 488 103 31, uae@championdoor.com

В Москве: 249000, Калужская область, г. Балабаново, 96-й км Киевского шоссе. тел. +7 (495) 540-43-06, rus@championdoor.com Branch Office US, Champion Door, 5100 Westheimer Rd., Suite 200, Houston TX 77056, Tel (713)-352-0403, us@championdoor.com